

TIMEWISE

32 Old Barn Road
Hawthorn Woods, Illinois 60047 USA
(847) 550-5052

PRICE LIST, DOMESTIC*

Effective March 14, 2022

MODEL	DESCRIPTION	PRICE
798A	Professional Rally Computer w/ Model 398-3 Driver's Display and Options 1, 3, 5, 6, 9, 10, 11, 17.....	\$1995.00
547B	Rally Odometer (Overall and Trip), Timer, & Clock; with 250 split memory	635.00
825	Analog Reading Electronic Speedometer; .0125 mph accuracy; 4.5" diameter.....	1125.00
660	Multi-split/Multi-Function Checkpoint Timer/Clock; with 75 split memory.....	285.00
397-3	Driver's Display for discontinued Models 797A and 796A; 3 ft cable (\$2.50/ft for add'l cable)	195.00
398-3	Driver's Display for Model 798A (replacement); 3 ft cable (\$2.50/ft for add'l cable).....	260.00
326-3	Driver's Display for Models 547B, & discontinued 747A and 526B; 3 ft cable (\$2.50/ft for add'l cable)	230.00

OPTIONS

Note: Some options are mutually exclusive and alter standard features. Call for details.

Additional \$125 to install one or more options not ordered with original purchase

798A/1	Datalog of last 56 CASTs and Splits.....	50.00
798A/2	Automatic reverse (off-course) when backing up (cable not included).....	75.00
798A/3	Adds Timer; simultaneous Error, Odo and Timer reset, splittable Error.....	37.50
798A/4	RS-232C interface	NA
798A/5	Include ability to adjust the auxiliary odometer	15.00
798A/6	Allows setting CASTs with .01 mph resolution	15.00
798A/7	Add ability to remotely select alternate parameter in driver's auxiliary display	50.00
798A/8	Rear panel BNC with 1 Hertz output synchronization signal.....	75.00
798A/9	Adjustable ERROR offset bias (-0.9 to +0.9).....	85.00
798A/10	Discretionary "Intelli-Fix" ORM correction during a LAST CAST adjustment.....	15.00
798A/11	Automatic CAST execution at a preset distance.....	15.00
798A/12	Locking Forward/Park/Reverse switch	15.00
798A/13	Remote reset of main Auxiliary display (replaces remote CAST, or add \$35 for additional input jack).....	15.00
798A/14	Short actuator on +/- 10.00 toggle switch	35.00
798A/15	Short actuator on Forward-Park-Reverse toggle switch.....	35.00
798A/16	Ability to remotely reset the Aux Odometer and automatically display it in the driver's module.....	50.00
798A/17	Ability to instantly truncate the Calculated Time minutes	45.00
798A/18F	Add front panel selection of Semi-Intelli-CAST (0.001) main odometer resolution upon a CAST.....	15.00
798A/18R	Add rear panel switch to select "normal" (0.0001) or Semi-Intelli-CAST (0.001) CAST resolution.....	50.00
547B/1	Battery backed Real Time Clock (RTC).....	20.00
547B/2	Built-in odometer input pulse divider ($\div 1$, $\div 2$, $\div 4$, $\div 8$, $\div 16$).....	27.00
547B/3	RS-232C printer output of Clock when Split activated.....	NA
547B/4	Remote Recall input connector installed.....	37.50
660/1	Install 6 - 9 volt DC input power jack allowing continuous backlighting of LCD display	25.00

ODOMETER INPUT SENSORS

217-15	Super-sensitive Permalloy sensor (to sense magnets); 8 contact RJ-45 modular plug; 15 ft.....	67.95
215.0-7	Speedometer cable sensor; 5/8" x 18 fittings; .105" square key; 8 cont. RJ-45 modular plug; 7 ft.....	121.50
215.1-7	Speedometer cable sensor; 7/8" x 18 fittings; .105" square key; 8 cont. RJ-45 modular plug; 7 ft.....	125.00
215.2-7	Speedo cable sensor; 5/8" x 18 male; 7/8" x 18 female; .105" sq. key; 8 cont. mod. RJ-45 plug; 7 ft.....	125.00
215.3-7	Speedo cable sensor; 18mm x 1.5mm fittings; .105" square key; 8 contact RJ-45 mod. plug; 7 ft.....	150.00
215.4-7	Speedo cable sensor; adaptable key size [†] ; 22mm x 1.5mm fittings; 8 contact mod. RJ-45 plug; 7 ft.....	150.00
215.5-7	Speedo cable sensor; adaptable key size [†] ; 7/8" x 18 fittings; 8 contact RJ-45 modular plug; 7 ft.....	135.00
-x	Additional cable length (replace -x with total length in feet).....	per additional foot, add 2.05
-pullup	Internal pull-up resistor on sensor output signal (1K ohm unless specified otherwise).....	add 2.25
-SR	Strain relief / protection tubing installed on speedometer cable sensor wiring.....	25.00
-RB	Rubber anti-snap protective boot installed on RJ-45 modular plug	8.00
	Replace 8 contact RJ-45 mod. plug w/ CINCH P-303-CCT plug or SWITCHCRAFT SL-403M plug ...	add 3.25
	Delete modular plug.....	subtract 3.75

[†] Requires one each of a male and female drive key. Specify either .105", .125", .150", or .187" square key or .152", .187", or .203" tang key. See accessories for part number and cost.

Contact TIMEWISE for adapters to other types and sizes of speedometer cable fittings and keys.

* Prices do not include shipping.

TIMEWISE domestic price list*, continued

Effective March 14, 2022

ODOMETER INPUT SENSOR ADAPTERS & EXTENSION CABLES

110-1	8 contact modular plug to "no connector" (cable blunt cut, then stripped and tined); 1 ft.....	5.80
111-1	8 contact modular plug to 8 contact modular plug; 1 ft.....	9.55
112-1	8 contact modular plug to SWITCHCRAFT SL-413F socket; 1 ft.....	12.80
113-1	8 contact modular plug to CINCH S-303-CCT socket; 1 ft.....	12.80
123-1	SWITCHCRAFT SL-403M plug to CINCH S-303-CCT socket; 1 ft.....	16.05
-x	Additional cable length (replace -x with total length in feet).....	per additional foot, add 2.05
-RB	Rubber anti-snag protective boot installed on RJ-45 modular plug.....	8.00
	Replace modular plug w/ CINCH P-303-CCT plug or SWITCHCRAFT SL-403M plug.....	add 3.25
	Delete modular plug.....	subtract 3.75

ACCESSORIES & SUPPLIES

405	Mounting bracket for Model 217 sensor (6" x 0.75" x 0.15"); 4 holes; zinc plated steel.....	4.00
406	Mounting bracket for Model 217 sensor (8" x 1.00" x 0.15"); 4 holes; tin plated copper.....	4.00
407	Mounting bracket for Model 217 sensor (4" x 1.00" x 0.15"); 2 holes; zinc plated steel.....	2.50
410	Magnets for Model 217 sensor; ceramic; 0.5" dia x 0.2"; pkg of 5; (from Radio Shack).....	5.75
410-1	Magnets for Model 217 sensor; high gauss C8 ceramic; 0.5" dia x 0.187"; each; red dot on South pole.....	1.15
410-2	Magnets for Model 217 sensor; ceramic; 7/8" x 1/4" x 5/16"; each; red dot on South pole.....	1.00
415	Replacement Ni-Cad battery (8.4 volt) for discontinued Model 526B.....	22.50
420-xxx	Instrument mounting bracket (replacement), specify model (-xxx indicates model).....	28.50
425	Plastic mounting knob for instrument mounting brackets (replacement).....	3.50
430	Hard rubber washer for instrument mounting brackets (replacement).....	0.75
431	Transducer hex nuts; Zinc plated steel, 1/8" IPS x 9/16" across flats x 3/16" thick.....	1.00
432	Transducer lockwasher; 3/8" inside toothed, zinc plated steel.....	0.10
435	.105" square drive key for Model 215.0/1/2/3 sensor (replacement).....	8.00
436-xxx	Male square drive key for Model 215.4/5 sensors‡ (-xxx indicates square pin size).....	10.00
437-xxx	Female square drive key for Model 215.4/5 sensors‡ (-xxx indicates square hole size).....	12.00
436-xxxT	Male tang drive key for Model 215.4/5 sensors‡ (-xxx indicates tang diameter size).....	12.00
437-xxxT	Female tang drive key for Model 215.4/5 sensors‡ (-xxx indicates tang hole size).....	14.00
440	Odometer Input Jumper Plug (replacement).....	3.75
450	8 contact modular jack in-line coupler to connect two 8 cont. mod. plugs straight through.....	9.50
455	Dust Cover Plug for unused 8 contact modular jacks (replacement on 547B).....	1.50
460	Handheld thumb activated pendant switch, medium duty; user connects to RCA jack at base of switch....	17.50
460-xxx	Handheld thumb activated pendant switch, medium duty; 6 ft cable; 1/8" stereo plug (specify application).....	43.00
461-xxx	Handheld thumb activated pendant switch, light duty; 4 ft cable; 1/8" stereo plug (specify application)....	30.50
462-xxx	Handheld index finger activated pendant switch, heavy duty; 6 ft cable; 1/8" stereo plug (specify app)....	55.00
465	Replacement DC power cable with in-line 3AG fuse holder & 2 amp fuse; 22 gauge wire; 3 ft.....	15.00
466	DC power extension cable; 18 gauge wire; 1 ft.....	4.00
467	Heavy duty DC power cable w/ plug dust cover, ATC/ATO blade style fuse holder & 2 amp fuse; 1.7 ft..	15.50
468-3.5	Heavy duty DC power extension cable; 3.5 ft.....	14.50
468-6	Heavy duty DC power extension cable; 6 ft.....	18.00
468-15	Heavy duty DC power extension cable; 15 ft.....	30.00
469	Heavy duty DC power "Y splitter" cable; 1 input to 2 outputs.....	13.00
469-F	Heavy duty DC power "Y splitter" cable; 1 input to 2 outputs each with in-line ATO/ATC blade fuses....	18.00
470	Right angle 1/8" stereo plug adapter.....	8.50
475	Right angle 1/8" stereo plug for remote control input.....	4.25
480	Clock synchronization cable, 1/8" stereo plug each end, 6 feet long.....	10.00
485	JB Weld epoxy for magnets.....	10.00
1001-x	User's Manual (replacement), specify model (-x indicates model).....	10.00

‡ specify: .105", .125", .150", or .187" square key or .152", .187", or .203" tang key

Contact TIMEWISE for adapters to other types and sizes of speedometer cable fittings and keys.

* Prices do not include shipping.